



35-9940



HANDY LIFT

Quality and utility without the expense. Features include:

- American made
- Heavy duty pneumatic cylinder
- Roller bearing slides
- 24 by 80 inch steel top with removable ramp
- Cast wheels allow shop movement
- 1,000 pound capacity
- Lifts up to 31 inches
- Foot pedal control

35-9060 Handy Lift only

35-9057 Electric Handy Lift only

OPTIONAL ACCESSORIES

35-9101 Cycle Vice (30 lbs)-clamps the bike to the steel bed.

35-9056 Side Panels (85 lbs)-extend the width of the lift's steel top to accommodate ATVs and snowmobiles.

35-9102 Single Wheel Dolly -(15 lbs.)

35-9064 13" Front Extension for Lift

35-9071 12" Side Extension for Lift

35-9046 Lift Foot Valve Assy.

35-9365 Cylinder Repair Kit-(seals only)



K&L LIFT-GATE

The newest accessory for the MC600 lift allows you to suspend the end on almost any type of vehicle, including Motorcycles, Snowmobiles, Watercraft, and ATV's. It can be used as a stand alone unit, or in conjunction with the MC600 lift to handle the longer wheelbases on today's motorcycles. The unit is constructed of 1.68" tubing and features three tie down points to secure the unit being serviced. It consists of three sections, and is UPS shippable. Overall assembled height is 79.5", width at base is 29.5". Increase the versatility of your service department! *Note:* Will not work on Full Dressed, Touring Motorcycles. Winch not included.

35-9940 K&L Lift-Gate

35-9952 Optional Winch, Cable included

35-9953 Cable only

K&L MC470 IN-GROUND LIFT ADAPTER PLATE

This plate mounts onto the in-ground lift and features 4 adjustable contact points. Slotted frame allows precise positioning. Bolts to 6-1/2" lifts only.



37-9899 In-ground lift adapter plate

BESTWAY IN GROUND LIFTS

These heavy duty, air/hydraulic motorcycle lifts are easily installed and require a 4-1/2" ft deep hole. Minimum height is 3", maximum rise above floor is 36". All units come complete with a three way valve for attaching air line to operate. Motorcycle lifts can be turned 360°. Lifting capacity is 1,200 lbs. for units with 5" pistons and 1,800 lbs for units with 6" piston. Lifts are supplied standard (no platform) with air valve installed on side. Add platform for needs of your service dept.

35-9315 Standard lift with 5" piston. 18" x 18" top plate dimension

35-9316 Standard lift for Harley-Davidson® service, 5" piston, 18" x 18" top plate dimension, comes with pre-drilled top designed for securing motorcycle frame to top of lift.

35-9317 Standard lift with 6-1/2" piston. 18" x 18" top plate dimension

35-9318 Standard lift for Harley Davidson® service, 6-1/2" piston, 18" x 18" top plate dimension, comes with pre-drilled top designed for securing motorcycle frame to top of lift.

35-9319 Harley-Davidson® platform 35-9315 and 35-9317

35-9321 Standard Casing-use for 35-9315 and 35-9316

35-9322 Standard Casing-use for 35-9317 and 35-9318