



IGNITION MATE

This dual-display peak voltage ignition tester shows constant signals (peak voltage) and pulsed signals (spark energy) at the same time. The Ignition Mate is compact, and uses either the 12V vehicle battery or its own internal battery source. Detailed instructions, impact resistant rubber holder and foam-lined storage case are included.

35-8315 Ignition Mate



OPPAMA PET-1100 PULSE ENGINE TACHOMETER

A hand held digital tachometer for monitoring two stroke engines (one through four cylinders) and four-stroke engines (one through six and eight cylinders). Just bring tachometer near to your engine and it will digitally show how fast engine is running by counting electric pulses from spark plug/spark plug cable, and give instantaneous RPM readings. A hanging cord and antenna lead jack with clip to connect directly to spark plug/spark plug cable are also included with each unit. RPM Display Interval: 0.5 seconds Dimensions: 120 x 62 x 13mm. Weight: 73g.

35-8313 Oppama Pet-1100 Pulse Engine Tachometer



35-7383



35-7386



35-7388

VERSA-TACH #321 DIGITAL ENGINE TEST TACHOMETER

Model #321 tachometer incorporates wireless capability as well as interchangeable capacitive and inductive secondary clamp pick-ups. The wireless features provide for quick RPM checks and readings where secondary leads are inaccessible. Selector switches allow for direct readings of two and four - cycle engines firing up to three times per crankshaft revolution. RPM switch selections are: 1 to 10,000 RPM in 10 RPM increments and 10 to 20,000 RPM in 100 RPM increments. Model #321 tachometer comes with inductive 10' inductive clip and hanger handle. Optional accessories available. One Year warranty.

35-7383 #321 Digital Engine Test Tachometer

Includes inductive 10' inductive clip and hanger handle. Optional accessories available.

SIZE: Approximately 3.375" wide x 4.625" high x 1.250" deep

POWER: (4) AAA 1.5 batteries

REPLACEMENT PARTS & OPTIONAL ACCESSORIES

35-7386 Inductive Clip-20 ' 35-7388 Vinyl Storage Case



FLUKE MODEL 88 MULTIMETER with TACHOMETER

Features include volt, ohm, amp, continuity and diode tests, RPM measurements with the provided inductive pickup, minimum/maximum/average recording of measurements, frequency and duty cycle measurements, low-ohms function, millisecond pulse width measurements, and smoothing (shows an averaged reading of measurements which fluctuate such as RPM). Included accessories; holster, inductive pickup, hard carrying case, test leads, test probes, large alligator clips, users manual and quick reference guide.

35-1927 Model 88 Multimeter with Tachometer



35-1931

35-1931 PV350 Pressure / Vacuum Module. Allows any DMM to take and display pressure readings from 0 to 350 psig (3.5 to 2400 kPa) and vacuum from 0 to 29.9" Hg (0 to 76cm Hg). Transducer features 1/4" male national pipe thread (NPT) fitting.